



Quick Start Guide

CEF© 🖉 🖉 🍰 Made in China

HGWIP-720



GIVES **PEACE OF MIND** WHEREVER YOU ARE











Welcome

Thank you for choosing HOMEGUARD. Getting starting is easy.

What's included

Part names & Functions



- Remote Controlled Pan & Tilt

Motorised lens can swing left & right (350°), up & down (90°), remotely controlled from your SmartPhone or other device

Wireless Transmission

The camera signal is transmitted wirelessly to your internet router, then onto the internet to share securely with your viewingdevice(s)

 Save to Micro SD Card Camera can save footage and stills to a micro SD card (up to 128GB capacity, not included)

Get the App

For the best experience, download the Homeguardcare app for your smartphone by scanning the QR code below or searching for "Homeguardcare" in the app store.











1. WPS configuration: to search available WPS AP 2. WiFi mode: to connect the available WiFi signal

1. RJ45 Connection: wired connected 2. WiFi connection is failed Internet connected

The device is not launched

Keep blue (Network status) Keep red (Working status)

The indicator is off



 Make sure you are within range of the same Wi-Fi network you'll use for your camera.



Camera Settings



< Back	Add Camera	
Name	Cam_349515	
CameralD	VIEW-349515-EP	ZST
Username	admin	
Password	*****	
LAN Search		
LAN Search		-

3 Enter the default

Password "123456"



Click the setting button

K Back Advanced Settings WiFi Setting User Setting Time Setting Alarm Setting FTP Setting Mail Setting SD/TF Setting OSD Setting Reboot Camera About Camera 2 Click "Advanced Settings" 3 Click "WiFi Setting"

Choose your home "Router" and type in the "Password"

.....

K Back Enter Password

Password

Don

OR YOU CAN CHOOSE One Key WiFi Connection



You're Done!

Congratulations! Your HOMEGUARD Camera is set up and ready to go.

- You can now safely disconnect your Ethernet cable.
- You are now free to position your camera anywhere in your home where you get a WiFi signal and view it
 remotely from anywhere in the world on your Smartphone or Tablet!
- Please remember to change your password in the Advanced Setting-User Setting.
 Record your new password here:

Before you begin your IP Camera Set up, please:

✓ Have your IP Camera and power adapter ready.

- ✓ Have your iOS / android device available to download the Homeguardcare app.
- ✓ Make sure you are within range of the same Wi-Fi network you'll use for your camera.
- ✓ Run the app and add camera by scan the QR code at the bottom of the camera; Then input the user name and password.
- ✓ Click "More", select "Wi-Fi Config", fill in the Wi-Fi password and click "Configuration".



Tips:

1. Please put your smartphone near to the router.

- 2. Input WiFi SSID and password, click config button, then WiFi setup is finished.
- When WiFi indicator flash slowly (camera will be in this status after powered-on and hold for 5 minutes), it means you can start config WiFi. After config is successful. WiFi indicator will flash fast for a while.

Live View

Tap the monitoring screen, the video menu action bar will appear.



1 Cruise Vertically 2 Cruise Horizontally 3 Menu 🙆 Flip 6 Mirror 6 Exit Snapshot to phone 8 Record to phone 2 Listen Off 🔟 Talk Off Contrast Brightness 13 Restore to Default Resolution QVGA/VGA/720p (15) Contract

Monitoring Options

For two-way audio, make the Listen/Talk ON; When talk, please press Hold Talk.
 Tap Menu you can turn ON/OFF the IR LED and Set or Call Preset (For PTZ camera).





View from Mac or Windows PC

Install Homeguardcare software for your Mac or Windows PC from the included CD.



Specifications



ltem	Description
Hardware Features	10/100Mbps RJ45 Port
	WI-FI Support
	Power Interface
	Reset Button
	Built-in Micro SD Socket
	Built-in Microphone and speaker
	Built-in PIR sensor
	3.5mm Audio Out Interface
	12 infrared LED, 8m Night Vision Range
Resolution	1280 x 720, 640 x 360, 320 x 180
Compression / Max Frame Rate	H.264/MJPEG, 30fps
Image Sensor / Lens	1/4" CMOS Sensor, f=3.6mm, F=2.0 Viewing Angle: 60°
Manual Pan / Tilt Range	Horizontal 350°, Vertical 90°
Motion Detection	Supported, Will Activate Camera
Security Protocols	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Camera Dimensions	105.6mm x 116.6mm x 126mm
Power Input	5V DC, < 6W